








	CoBAM® Standard - Select 65333 3202	CoBAM® Exclusive - Select 65390 3202	CoBAM® Exclusive Light - Select 65503 3402	CoBAM® XL - Select 65555 3202	CoBAM® Mokka 65482 3302
Material Material Matériel:	bis zu 15 % Bindemittel; mind. 85 % Bambusfasern up to 15% binder agent; min. 85% bamboo fibers jusqu'à 15% de liant ; min. 85% de fibres de bambou				
Beschreibung Description Description:	fein geriffelt / grob genutet grooved / fine ribbed rainuré gros / rainuré fin coffee vorgeölt pre-oiled pré-huilé ~ 7 m/m²	französisch geriffelt / glatt gehobelt french-style / smooth double-peigne / lisse coffee vorgeölt pre-oiled pré-huilé ~ 7 m/m²	französisch geriffelt / glatt gehobelt french-style / smooth double-peigne / lisse natur vorgeölt pre-oiled pré-huilé ~ 7 m/m²	beidseitig grob genutet both sides grooved double face rainuré gros coffee vorgeölt pre-oiled pré-huilé ~ 5,5 m/m²	grob genutet / glatt gehobelt grooved / smooth rainuré gros / lisse mokka vorgeölt pre-oiled pré-huilé ~ 7 m/m²
Abmessungen Dimensions Dimensions:	± 2200 x 140 x 20 mm 	± 2200 x 140 x 20 mm 	± 2200 x 140 x 20 mm 	± 2200 x 180 x 22 mm 	± 1850 x 137 x 20 mm 
Menge und Gewicht pro Karton Quantity and weight per box Quantité et poids par carton:	3 x = 0,924 m² = ~ 22,57 kg	3 x = 0,924 m² = ~ 22,57 kg	3 x = 0,924 m² = ~ 22,57 kg	3 x = 1,188 m² = ~ 31,92 kg	3 x = 0,253 m² = ~ 6,21 kg
Menge und Gewicht pro Palette Quantity and weight per pallet Quantité et poids par palette:	135 x = ± 41,58 m² = ~ 1016,10 kg	135 x = ± 41,58 m² = ~ 1016,10 kg	135 x = ± 41,58 m² = ~ 1016,10 kg	96 x = ± 38,016 m² = ~ 1021,45 kg	192 x = ± 48,662 m² = ~ 1192,89 kg
Flächengewicht (ohne UK) grammage (without SK grammages (sans SK):	1 m² = ± 24,43 kg	1 m² = ± 24,43 kg	1 m² = ± 24,43 kg	1 m² = ± 26,9 kg	1 m² = ± 24,5 kg

Eigenschaften Characteristics Propriétés	CoBAM® Standard - Select 65333 3202	CoBAM® Exclusive - Select 65390 3202	CoBAM® Exclusive Light - Select 65503 3402	CoBAM® XL - Select 65555 3202	CoBAM® Mokka 65482 3302
Zertifikate / Tests certificates / tests certificats / tests	VOC-Test nach AgBB-Schema				
Rohdichte gross density densité brute	1200 kg/m³				
Rutschhemmung Slip resistance Résistance au glissement	C; R10				
Brandschutzklasse fire-resistance class catégorie de résistance au feu	B _{fi} - S1				
Dauerhaftigkeitsklasse durability class catégorie de durabilité	1 - 2				
Formaldehydemission / Emission of formaldehyd / Emission de formaldéhyde	E1				

Hinweise recommendations recommandations*	CoBAM® Standard - Select 65333 3202	CoBAM® Exclusive - Select 65390 3202	CoBAM® Exclusive Light - Select 65503 3402	CoBAM® XL - Select 65555 3202	CoBAM® Mokka 65482 3302
Zugelassene UK approved sub-construction sous-construction autorisées	UK CoBAM; UK CoBAM Slim; Classico UK FSC 100%				
UK-Abstand distance sub-construction distance sous-construction	400 mm	400 mm	400 mm	450 mm	400 mm
Zugelassenes Montagematerial approved assembly material matériel de montage	Edelstahl-Clipset (schwarz) / -Schrauben stainless steel clips / screws clip en acier inoxydable / vis				
Empfohlenes Gefälle in Längsrichtung recommended slope lengthwise pente longitudinale recommandée	1,5 - 2 %				
Quergefälle möglich? cross slope possible? pente transversale possible?	nicht möglich not possible pas possible				
Mindestfugenabstand längs minimum joint distance lengthwise minimal espacement longitudinal	5 mm				
Mindestfugenabstand Stoss minimum short-end joints minimal espacement aux extrémités	Endlosmontage endless assembly montage sin fin				
Abstand zu festen Baukörpern distance to solid construction components espacement de solide construction	20 mm				
Empfohlene Reiniger recommended cleaner nettoyant recommandé	elephant Reiniger cleaner nettoyant				
Empfohlene Pflege recommended maintenance products entretien recommandé	elephant Bambuspflgeöl / elephant Bambus Hirnholzschutz bamboo maintenance oil special / bamboo cross-cut wood protection huile d'entretien spéciale bambou / bambou protection bois de bout				